



Numero di parte	d [mm]	D [mm]	W [mm]	Peso [g]	Velocità [rpm]	Carico statico (kN)
6000HT800	10	26	8	20	295	1.14
6001HT800	12	28	8	25	275	1.37
6002HT800	15	32	9	30	265	1.65
6003HT800	17	35	10	40	250	1.88
6004HT800	20	42	12	69	240	2.89
6005HT800	25	47	12	80	180	3.38
6006HT800	30	55	13	120	150	4.62
6007HT800	35	62	14	160	125	6.01
6008HT800	40	68	15	190	115	6.8
6009HT800	45	75	16	250	100	8.27
6010HT800	50	80	16	260	90	9.02
6011HT800	55	90	18	390	85	12.26
6012HT800	60	95	18	420	80	13.43
6013HT800	65	100	18	440	70	14.45
6014HT800	70	110	20	600	68	18.21
6015HT800	75	115	20	640	63	19.65
6016HT800	80	125	22	850	55	22.1
6017HT800	85	130	22	890	55	23.7
6018HT800	90	140	24	1150	55	27.6
6200HT800	10	30	9	30	275	1.5

800°C high temperature bearings

6201HT800	12	32	10	37	265	1.79
6202HT800	15	35	11	45	250	2.17
6203HT800	17	40	12	65	220	2.75
6204HT800	20	47	14	110	170	3.79
6205HT800	25	52	15	130	160	4.62
6206HT800	30	62	16	200	120	6.48
6207HT800	35	72	17	290	110	8.5
6208HT800	40	80	18	370	95	10.4
6209HT800	45	85	19	410	90	11.79
6210HT800	50	90	20	460	80	13.86