

Ceramic Thrust Ball Bearings



Numero di parte	ID	OD	Larghezza	Carico dinamico	Carico statico	Velocità massima (X1K giri/min)	Tipo	Misurazione	Direzione del carico	Materiale della rondella	Materiale della palla	Materiale della gabbia	Intervallo di temperatura	RoHS	PORTATA
51314	70 mm	125 mm	40 mm	238700 N	107100 N	3	Ball	Metric	Thrust	Ceramic	Ceramic	PEEK	[-176 to 752 °F	Compliant	Compliant
51214	70 mm	105 mm	27 mm	132300 N	50960 N	5	Ball	Metric	Thrust	Ceramic	Ceramic	PEEK	[-176 to 752 °F	Compliant	Compliant
51114	70 mm	95 mm	18 mm	79100 N	27510 N	5	Ball	Metric	Thrust	Ceramic	Ceramic	PEEK	[-176 to 752 °F	Compliant	Compliant
51413m	65 mm	140 mm	56 mm	314300 N	151900 N	3	Ball	Metric	Thrust	Ceramic	Ceramic	PEEK	[-176 to 752 °F	Compliant	Compliant
51413	65 mm	140 mm	56 mm	345800 N	161700 N	3	Ball	Metric	Thrust	Ceramic	Ceramic	PEEK	[-176 to 752 °F	Compliant	Compliant
51313m	65 mm	115 mm	36 mm	186900 N	84700 N	3	Ball	Metric	Thrust	Ceramic	Ceramic	PEEK	[-176 to 752 °F	Compliant	Compliant
51313	65 mm	115 mm	36 mm	200900 N	88900 N	3	Ball	Metric	Thrust	Ceramic	Ceramic	PEEK	[-176 to 752 °F	Compliant	Compliant
51213	65 mm	100 mm	27 mm	133700 N	54950 N	5	Ball	Metric	Thrust	Ceramic	Ceramic	PEEK	[-176 to 752 °F	Compliant	Compliant
51113	65 mm	90 mm	18 mm	75600 N	27440 N	5	Ball	Metric	Thrust	Ceramic	Ceramic	PEEK	[-176 to 752 °F	Compliant	Compliant
51412m	60 mm	130 mm	51 mm	282800 N	144200 N	3	Ball	Metric	Thrust	Ceramic	Ceramic	PEEK	[-176 to 752 °F	Compliant	Compliant
51412	60 mm	130 mm	51 mm	314300 N	155400 N	3	Ball	Metric	Thrust	Ceramic	Ceramic	PEEK	[-176 to 752 °F	Compliant	Compliant
51312m	60 mm	110 mm	35 mm	172200 N	81200 N	3	Ball	Metric	Thrust	Ceramic	Ceramic	PEEK	[-176 to 752 °F	Compliant	Compliant
51312	60 mm	110 mm	35 mm	186900 N	86100 N	3	Ball	Metric	Thrust	Ceramic	Ceramic	PEEK	[-176 to 752 °F	Compliant	Compliant
51212m	60 mm	95 mm	26 mm	111300 N	47320 N	5	Ball	Metric	Thrust	Ceramic	Ceramic	PEEK	[-176 to 752 °F	Compliant	Compliant
51212	60 mm	95 mm	26 mm	198300 N	49280 N	5	Ball	Metric	Thrust	Ceramic	Ceramic	PEEK	[-176 to 752 °F	Compliant	Compliant
51112	60 mm	85 mm	17 mm	69020 N	26530 N	6	Ball	Metric	Thrust	Ceramic	Ceramic	PEEK	[-176 to 752 °F	Compliant	Compliant
51411m	55 mm	120 mm	48 mm	250600 N	134400 N	3	Ball	Metric	Thrust	Ceramic	Ceramic	PEEK	[-176 to 752 °F	Compliant	Compliant
51311m	55 mm	105 mm	35 mm	158200 N	77700 N	3	Ball	Metric	Thrust	Ceramic	Ceramic	PEEK	[-176 to 752 °F	Compliant	Compliant
51311	55 mm	105 mm	35 mm	172200 N	82600 N	3	Ball	Metric	Thrust	Ceramic	Ceramic	PEEK	[-176 to 752 °F	Compliant	Compliant
51211	55 mm	90 mm	25 mm	111300 N	48160 N	5	Ball	Metric	Thrust	Ceramic	Ceramic	PEEK	[-176 to 752 °F	Compliant	Compliant
51111	55 mm	78 mm	16 mm	57050 N	21770 N	6	Ball	Metric	Thrust	Ceramic	Ceramic	PEEK	[-176 to 752 °F	Compliant	Compliant
51410m	50 mm	110 mm	43 mm	191800 N	103600 N	3	Ball	Metric	Thrust	Ceramic	Ceramic	PEEK	[-176 to 752 °F	Compliant	Compliant
51310	50 mm	95 mm	31 mm	141400 N	66710 N	5	Ball	Metric	Thrust	Ceramic	Ceramic	PEEK	[-176 to 752 °F	Compliant	Compliant
51210	50 mm	78 mm	22 mm	90300 N	39410 N	5	Ball	Metric	Thrust	Ceramic	Ceramic	PEEK	[-176 to 752 °F	Compliant	Compliant
51110	50 mm	70 mm	14 mm	52850 N	19670 N	6	Ball	Metric	Thrust	Ceramic	Ceramic	PEEK	[-176 to 752 °F	Compliant	Compliant
51409m	45 mm	100 mm	39 mm	165200 N	91700 N	3	Ball	Metric	Thrust	Ceramic	Ceramic	PEEK	[-176 to 752 °F	Compliant	Compliant

Ceramic Thrust Ball Bearings

51409	45 mm	100 mm	39 mm	183400 N	98000 N	3	Ball	Metric	Thrust	Ceramic	Ceramic	PEEK	[-176 to 752 °F	Compliant	Compliant
51309	45 mm	85 mm	28 mm	114800 N	55230 N	5	Ball	Metric	Thrust	Ceramic	Ceramic	PEEK	[-176 to 752 °F	Compliant	Compliant
51209	45 mm	73 mm	20 mm	78400 N	34510 N	6	Ball	Metric	Thrust	Ceramic	Ceramic	PEEK	[-176 to 752 °F	Compliant	Compliant
51109m	45 mm	65 mm	14 mm	39620 N	16660 N	8	Ball	Metric	Thrust	Ceramic	Ceramic	PEEK	[-176 to 752 °F	Compliant	Compliant