

Inch Standard



Numero di parte	Materiale dell'anello	ID	OD	Larghezza	Tipo di scudo	Carico dinamico	Carico statico	Velocità limitata (x1K rpm)	Sistema di Misurazione	Tipo di cuscinetto	Tipo a cuscinetti a sfera	Costruzione	Precisione	Sgombero	Intervallo di temperatura	RoHS	SGS
R2zz	52100 Chrome Steel	0.125"	0.375"	0.1562"	Shielded	121 lbf	39 lbf	56	Inch	Ball	Standard	Single Row	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
SR2Azz	440C Stainless Steel	0.125"	0.5"	0.1719"	Shielded	110 lbf	37 lbf	47.7	Inch	Ball	Standard	Single Row	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
R2Azz	52100 Chrome Steel	0.125"	0.5"	0.1719"	Shielded	122 lbf	41 lbf	53	Inch	Ball	Standard	Single Row	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
SR2A 2rs	440C Stainless Steel	0.125"	0.5"	0.1719"	Sealed	110 lbf	37 lbf	47.7	Inch	Ball	Standard	Single Row	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
R2A 2rs	52100 Chrome Steel	0.125"	0.5"	0.1719"	Sealed	122 lbf	41 lbf	53	Inch	Ball	Standard	Single Row	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
SR2A	440C Stainless Steel	0.125"	0.5"	0.1719"	Open	110 lbf	37 lbf	47.7	Inch	Ball	Standard	Single Row	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
R2A	52100 Chrome Steel	0.125"	0.5"	0.1719"	Open	122 lbf	41 lbf	53	Inch	Ball	Standard	Single Row	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
SR2-6zz	440C Stainless Steel	0.125"	0.375"	0.1406"	Shielded	110 lbf	37 lbf	47.7	Inch	Ball	Standard	Single Row	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
R2-6zz	52100 Chrome Steel	0.125"	0.375"	0.1406"	Shielded	122 lbf	41 lbf	53	Inch	Ball	Standard	Single Row	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
SR2-6 2rs	440C Stainless Steel	0.125"	0.375"	0.1406"	Sealed	110 lbf	37 lbf	47.7	Inch	Ball	Standard	Single Row	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
R2-6 2rs	52100 Chrome Steel	0.125"	0.375"	0.1406"	Sealed	122 lbf	41 lbf	53	Inch	Ball	Standard	Single Row	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
SR2-6	440C Stainless Steel	0.125"	0.375"	0.1094"	Open	110 lbf	37 lbf	47.7	Inch	Ball	Standard	Single Row	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
R2-6	52100 Chrome Steel	0.125"	0.375"	0.1094"	Open	122 lbf	41 lbf	53	Inch	Ball	Standard	Single Row	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
SR2-5zz	440C Stainless Steel	0.125"	0.3125"	0.1406"	Shielded	96 lbf	29 lbf	54	Inch	Ball	Standard	Single Row	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
R2-5zz	52100 Chrome Steel	0.125"	0.3125"	0.1406"	Shielded	107 lbf	32 lbf	60	Inch	Ball	Standard	Single Row	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
SR2-5 2rs	440C Stainless Steel	0.125"	0.3125"	0.1406"	Sealed	96 lbf	29 lbf	54	Inch	Ball	Standard	Single Row	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
R2-5 2rs	52100 Chrome Steel	0.125"	0.3125"	0.1406"	Sealed	107 lbf	32 lbf	60	Inch	Ball	Standard	Single Row	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
SR2-5	440C Stainless Steel	0.125"	0.3125"	0.1094"	Open	96 lbf	29 lbf	54	Inch	Ball	Standard	Single Row	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
R2-5	52100 Chrome Steel	0.125"	0.3125"	0.1094"	Open	107 lbf	32 lbf	60	Inch	Ball	Standard	Single Row	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
SR2 2rs	440C Stainless Steel	0.125"	0.375"	0.1562"	Sealed	109 lbf	35 lbf	50.4	Inch	Ball	Standard	Single Row	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
R2 2rs	52100 Chrome Steel	0.125"	0.375"	0.1562"	Sealed	121 lbf	39 lbf	56	Inch	Ball	Standard	Single Row	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
SR2	440C Stainless Steel	0.125"	0.375"	0.1562"	Open	109 lbf	35 lbf	50.4	Inch	Ball	Standard	Single Row	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
R2	52100 Chrome Steel	0.125"	0.375"	0.1562"	Open	121 lbf	39 lbf	56	Inch	Ball	Standard	Single Row	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant

Inch Standard

SR144zz	440C Stainless Steel	0.125"	0.25"	0.1094"	Shielded	49 lbf	15 lbf	60.3	Inch	Ball	Standard	Single Row	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
R144zz	52100 Chrome Steel	0.125"	0.25"	0.1094"	Shielded	54 lbf	17 lbf	67	Inch	Ball	Standard	Single Row	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
SR144 2rs	440C Stainless Steel	0.125"	0.25"	0.1094"	Sealed	49 lbf	15 lbf	60.3	Inch	Ball	Standard	Single Row	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
R144 2rs	52100 Chrome Steel	0.125"	0.25"	0.1094"	Sealed	54 lbf	17 lbf	67	Inch	Ball	Standard	Single Row	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
SR144	440C Stainless Steel	0.125"	0.25"	0.0937"	Open	49 lbf	15 lbf	60.3	Inch	Ball	Standard	Single Row	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
R144	52100 Chrome Steel	0.125"	0.25"	0.0937"	Open	54 lbf	17 lbf	67	Inch	Ball	Standard	Single Row	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant
SR133zz	440C Stainless Steel	0.09375"	0.1875"	0.0937"	Shielded	25 lbf	9 lbf	72	Inch	Ball	Standard	Single Row	ABEC-1/P0	C0	-30° to 110°C	Compliant	Compliant